

Enphase IQ Battery 10T

The **Enphase IQ Battery 10T** all-in-one AC-coupled storage system is **reliable, smart, simple, and safe**. It is comprised of three base IQ Battery 3T storage units, has a total usable energy capacity of 10.08 kWh and twelve embedded grid-forming microinverters with 3.84 kW power rating. It provides backup capability and installers can quickly design the right system size to meet the needs of both new and retrofit solar customers.



Reliable

- Proven high reliability IQ series microinverters
- Ten-years limited warranty, extendable to 15 years¹
- Three independent IQ Battery base units
- Twelve embedded IQ8X-BAT microinverters
- Passive cooling (no moving parts/fans)

Smart

- Grid-forming capability for backup operation
- Remote software and firmware upgrade
- Mobile app-based monitoring and control
- Support for self consumption
- Utility time of use (TOU) optimization

Simple

- Fully integrated AC battery system
- Quick and easy plug-and-play installation
- Interconnects with standard household AC wiring

Safe

- Safety tested battery cells and module
- Lithium iron phosphate (LFP) chemistry for maximum safety and longevity

Enphase IQ Battery 10T

MODEL NUMBER	
ENCHARGE-10T-1P-NA	IQ Battery 10T Battery storage system with integrated Enphase IQ series microinverters and battery management unit (BMU). Includes: - Three IQ Battery 3T base units (B03-T01-US00-1-3) - One IQ Battery 10T cover kit with cover, wall mounting bracket, and interconnect cable for wiring between batteries (B10T-C-1290-O)
OUTPUT (AC)	
	@ 240 VAC ²
Rated (continuous) output power	3.84 kVA
Peak output power	5.76 kVA (10 seconds)
Nominal voltage / range	240 / 211 – 264 VAC
Nominal frequency / range	60 / 57 – 63 Hz
Rated output current	16 A
Peak output current	24.6A (10 seconds)
Power factor (adjustable)	0.85 leading ... 0.85 lagging
Maximum units per 20 A branch circuit	1 unit (single phase)
Interconnection	Single-phase
Maximum AC short circuit fault current over 3 cycles	69.6 Arms
Round trip efficiency ³	89%
BATTERY	
Total capacity	10.5 kWh
Usable capacity	10.08 kWh
Round trip efficiency	96%
Nominal DC voltage	67.2 V
Maximum DC voltage	75.6 V
Ambient operating temperature range	-15° C to 55° C (5° F to 131° F) non-condensing
Optimum operating temperature range	0° C to 30° C (32° F to 86° F)
Chemistry	Lithium iron phosphate (LFP)
MECHANICAL DATA	
Dimensions (WxHxD)	1283 x 775 x 188 mm (50.5 x 30.5 x 7.4 in)
Weight	Three individual 40.5 kg (89.3 lbs) base units plus 22.1 kg (48.7 lbs) cover and mounting bracket; total 143.6 kg (316.5 lbs)
Enclosure	Outdoor – NEMA type 3R
IQ8X-BAT microinverter enclosure	NEMA type 6
Cooling	Natural convection – No fans
Altitude	Up to 2500 meters (8200 feet)
Mounting	Wall mount
FEATURES AND COMPLIANCE	
Compatibility	Compatible with grid-tied PV systems. Compatible with Enphase M215/M250 and IQ Series Micros, Enphase IQ System Controller, and Enphase IQ Gateway for backup operation.
Communication	Wireless 2.4 GHz
Services	Backup, self-consumption, TOU, Demand Charge, NEM Integrity
Monitoring	Enphase Installer Platform monitoring options; API integration
Compliance	UL9540, UL9540A ⁴ , UN 38.3, UL 1998, UL 991, NEMA Type 3R, AC156 EMI: 47 CFR, Part 15, Class B, ICES 003 Cell Module: UL 1973, UN 38.3 Inverters: UL 62109-1, IEC 62109-2, UL 1741SA, CAN/CSA C22.2 No. 107.1-16, and IEEE 1547
LIMITED WARRANTY	
Limited Warranty	>70% capacity, up to 10 years or 4000 cycles ⁵ , extendable to 15 years ¹

1. Terms and conditions apply.
2. Supported in both grid-connected and backup operation.
3. AC to Battery to AC at 50% power rating.
4. When installed with Wall Mount SKUs (B10T-AWM-1280-O & B10T-MWM-1280-O). See [IQ Battery 3T/10T Installation Guide](#) for details.
5. Whichever occurs first. Restrictions apply.