

K2C12V4A SMART CHARGER

KEY FEATURES AND BENEFITS

- Short Circuit Protection
- Over Current Protection
- Charging LED Indicator Light
- Compact and Lightweight Portability
- Reverse Polarity & Auto Recovery

ADVANTAGES

Multiple K2 Battery Compatibility:
 Quick Charge Times
 Custom Terminals Available
 K2B12V7 | K2B12V10 | K2B12V19 | K212VG27-3
 (Contact K2 representative for additional battery compatibility usage)



DESCRIPTION

AC Input Voltage	50 / 60Hz 100-240 VAC
AC Input Current	1.8 A
Output Voltage	DC 14.6 V
Output Load	4.0 A Max

OPERATING CONDITIONS

CC / CV (Constant Current / Constant Voltage)

Operating Temperature	0° - 40° C
Storage Temperature	-20° - 60° C
Operating Humidity	5% - 65% RH
Storage Humidity	5% - 65% RH
Caution	Indoor use only - K2 LiFeP04 batteries only
Dimensions	5.5 in. x 2.4 in. x 1.8 in. - (140mm*62mm*35mm)
Terminal Options	2 Pin SAE plug / Alligator Clips / Pigtails
Safety Rating	CE UL FCC RoHS PSE

K2 Terminals


(Custom terminals available - contact K2 for more info)

K2C12V4A_00 SAE

- 01 Pig Tails
- 02 Fasten 250
- 03 Alligator clips
- 05 Ring Terminals



00 SAE




01 Pig Tail leads



02 Fasten 250 (F)



03 Alligator Clips



Inner M-6 | Outer 12 mm

05 Ring Terminals