



**MODEL ER18505**  
**Lithium Thionyl Chloride**  
**(Li-SOCl<sub>2</sub>) Battery**  
 (International size reference: A, ER18505)

## ELECTRICAL CHARACTERISTICS

(Typical values for cells stored for one year or less, at +30°C max.)

■ **Nominal capacity** **4.0Ah**  
 (At 3.0 mA +20°C 2.0V cut off. The capacity restored by the cell varies according to current drain, temperature and cut off voltage.)

■ **Nominal voltage** **3.6 V**

■ **Maximum recommended continuous current** **130 mA**  
 (Higher currents possible, consult OmniCel)

■ **Maximum pulse capability** **Typically up to 180 mA**

■ **Storage** (Recommended) **+30°C max.**  
 (For more severe condition consult OmniCel)

■ **Operating temperature range** **-55°C / +85°C**  
 (Operation at temperature different from ambient may lead to reduced capacity and lower voltage plateau readings.)

## KEY FEATURES

- ✓ High and stable operating voltage
- ✓ High minimum voltage during pulsing
- ✓ Low self discharge rate (less than 1% after 1 year of storage at +25°C)
- ✓ Stainless steel container
- ✓ Hermetic glass-to-metal sealing
- ✓ Non-flammable electrolyte
- ✓ Restricted for transport (class 9)
- ✓ Compliant with IEC 60086-4 safety standard and EN 60079-11 intrinsic safety standard
- UL Underwriters Laboratories (UL) Component Recognition (File Number MH 28717)

## MAIN APPLICATIONS

- ✓ Utility metering
- ✓ Alarms and security devices
- ✓ Memory back-up
- ✓ Tracking systems
- ✓ Automotive electronics
- ✓ Professional electronics ... etc.

### ⚠ WARNING:

Fire, explosion and severe burn hazard. Do not recharge, crush, disassemble, heat above 212°F (100°C), incinerate, or expose contents to water. Do not solder directly to the cell, use tabbed cell instead.