



**12V//14V//16V**  
**AGMPOWERCELLS**

SEALED NON-SPILLABLE LEAD ACID BATTERIES AND ACCESSORIES

# REAL POWER UNREAL PERFORMANCE

Check Out Our Entire Line of XS Power Mobile Audio Products at [XSPOWERBATTERIES.COM](http://XSPOWERBATTERIES.COM)

**MAX Amps Explained:** CA and CCA have been used since 1914 as a definition for battery performance. CA is defined as a measurement of the number of amps a 12V battery can deliver for 30 seconds at 32 degrees F and not drop below 7.2 volts. CCA is the same test at 0 degrees F. These tests were designed for the cars of yesteryear that had to be cranked for a long time to get started. Back then, CA and CCA numbers were very meaningful. However for mobile audio use, immediate burst output is more important. XS Power batteries when compared to the batteries of yesteryear deliver much more of their power quickly. This instant burst of energy we call "max amps".

SECONDARY WATTAGE INDICATOR

600W ————— 3000W



## D375 / 12V AGM

12 Volt High Performance AGM Power Cell

**MAX AMP : 800**

CA : 300A RC : 25min Ah : 17

L: 7.87" (200mm)

W: 3.03" (77mm)

H: 5.28" (134mm)

Weight: 11.5lbs (5.2kg)

600Watts



## D545 / 12V AGM

12 Volt High Performance AGM Power Cell

**MAX AMP : 800**

CA : 276A RC : 22min Ah : 17

L: 6.97" (177mm)

W: 3.38" (86mm)

H: 5.14" (131mm)

Weight: 11.24lbs (5.1kg)

600Watts



## D680 / 12V AGM

12 Volt High Performance AGM Power Cell

**MAX AMP : 1000**

CA : 370A RC : 24min Ah : 20

L: 7.13" (181mm)

W: 3.03" (77mm)

H: 6.57" (167mm)

Weight: 13.69lbs (6.2kg)

1000Watts



## D925 / 12V AGM

12 Volt High Performance AGM Power Cell

**MAX AMP : 2000**

CA : 641A RC : 59min Ah : 32

L: 6.5" (165mm)

W: 6.93" (176mm)

H: 4.92" (125mm)

Weight: 22.26lbs (10.1kg)

2000Watts



## D950 / 12V AGM

12 Volt High Performance AGM Power Cell

**MAX AMP : 2100**

CA : 605A RC : 58min Ah : 40

L: 9.8" (249mm)

W: 3.8" (97mm)

H: 5.77" (147mm)

Weight: 26.43lbs (12kg)

2000Watts



## D975 / 12V AGM

12 Volt High Performance AGM Power Cell

**MAX AMP : 2100**

CA : 604A RC : 72min Ah : 43

L: 7.83" (199mm)

W: 5.3" (135mm)

H: 6.08" (170mm)

Weight: 26.5lbs (12.95kg)

2000Watts



## D1200 / 12V AGM

12 Volt High Performance AGM Power Cell

**MAX AMP : 2600**

CA : 740A RC : 95min Ah : 55

L: 7.79" (198mm)

W: 6.54" (166mm)

H: 6.09" (170mm)

Weight: 35.3lbs (16kg)

3000Watts



## D4700 / 12V AGM

12 Volt High Performance AGM Power Cell

**MAX AMP : 2900**

CA : 760A RC : 110min Ah : 62

L: 9.49" (241mm)

W: 6.93" (176mm)

H: 7.48" (190mm)

Weight: 41.19lbs (19.14kg)

3000Watts



(U5100R available)(R denotes reversed polarity)

## D5100 / 12V AGM

12 Volt High Performance AGM Power Cell

**MAX AMP : 3100**

CA : 872A RC : 131min Ah : 86

L: 9.04" (230mm)

W: 5.43" (138mm)

H: 8.19" (208mm)

Weight: 43.2lbs (19.6kg)

3000Watts



## D4800 / 12V AGM

12 Volt High Performance AGM Power Cell

**MAX AMP : 3000**

CA : 950A RC : 132min Ah : 74

L: 10.94" (299.72mm)

W: 6.93" (182.87mm)

H: 7.48" (172.72mm)

Weight: 48.2lbs (21.87kg)

3000Watts



(D3400R available)(R denotes reversed polarity)

## D3400 / 12V AGM

12 Volt High Performance AGM Power Cell

**MAX AMP : 3300**

CA : 1150A RC : 160min Ah : 80

L: 10.24" (260mm)

W: 6.89" (175mm)

H: 7.16" (182mm)

Weight: 49.97lbs (22.67kg)

4000Watts



## D2400 / 12V AGM

12 Volt High Performance AGM Power Cell

**MAX AMP : 3500**

CA : 1200A RC : 186min Ah : 96

L: 10.24" (260mm)

W: 6.65" (169mm)

H: 8.31" (211mm)

Weight: 59.5lbs (27kg)

4000Watts



**D7500 / 12V AGM**  
 12 Volt High Performance AGM Power Cell  
**MAX AMP : 6000**  
 CA : 2050A RC : 374min Ah : 172  
 L: 13.35" (339mm)  
 W: 6.81" (173mm)  
 H: 10.91" (277mm)  
 Weight: 99.65lbs (45.6kg)  
 7500Watts



**D4900 / 12V AGM**  
 12 Volt High Performance AGM Power Cell  
**MAX AMP : 4000**  
 CA : 1250A RC : 178min Ah : 100  
 L: 13.9" (353mm)  
 W: 6.63" (176mm)  
 H: 7.48" (190mm)  
 Weight: 63.8lbs (28.9kg)  
 4000Watts



**D6500 / 12V AGM**  
 12 Volt High Performance AGM Power Cell  
**MAX AMP : 3900**  
 CA : 1100A RC : 174min Ah : 86  
 L: 11.8" (300mm)  
 W: 7.20" (183mm)  
 H: 6.8" (173mm)  
 Weight: 53.8lbs (24.4kg)  
 4000Watts



**D2700 / 12V AGM**  
 12 Volt High Performance AGM Power Cell  
**MAX AMP : 4300**  
 CA : 1300A RC : 239min Ah : 113  
 L: 12.1" (307mm)  
 W: 6.65" (169mm)  
 H: 8.3" (211mm)  
 Weight: 69.89lbs (31.7kg)  
 4500Watts



**D3100 / 12V AGM**  
 12 Volt High Performance AGM Power Cell  
**MAX AMP : 5000**  
 CA : 1564A RC : 273min Ah : 127  
 L: 12.99" (329.9mm)  
 W: 6.81" (173mm)  
 H: 8.43" (214.1mm)  
 Weight: 78.3lbs (35.5kg)  
 5000Watts

## 14V / 16V POWER CELLS



**D1400 / 14V AGM**  
 14 Volt High Performance AGM Power Cell  
**MAX AMP : 2400**  
 CA : 775A RC : 96min Ah : 56  
 L: 10.24" (260mm)  
 W: 6.46" (164mm)  
 H: 7.20" (183mm)  
 Weight: 41.98lbs (19kg)



**D14-31 / 14V AGM**  
 14 Volt High Performance AGM Power Cell  
**MAX AMP : 5000**  
 CA : 1130A RC : 197min Ah : 98  
 L: 12.99" (329.9mm)  
 W: 6.81" (173mm)  
 H: 8.43" (214.1mm)  
 Weight: 71.65lbs (32.5kg)



**D1600 / 16V AGM**  
 16 Volt High Performance AGM Power Cell  
**MAX AMP : 2400**  
 CA : 775A RC : 96min Ah : 56  
 L: 10.24" (260mm)  
 W: 6.46" (164mm)  
 H: 7.20" (183mm)  
 Weight: 46.82lbs (21.24kg)



**D16-31 / 16V AGM**  
 16 Volt High Performance AGM Power Cell  
**MAX AMP : 5000**  
 CA : 1130A RC : 197min Ah : 98  
 L: 12.99" (329.9mm)  
 W: 6.81" (173mm)  
 H: 8.43" (214.1mm)  
 Weight: 80lbs (36.3kg)

GENUINE XS POWER  
CHARGERS AND ACCESSORIES



**HF1215** \*240V models available upon request  
Compact High Frequency AGM IntelliChargers  
15AMP Max Output. 12V, 14V and 16V Models Available



**1004**  
16V AGM IntelliCHARGER - 20AMP Max Output



**1005** \*1005E model not shown, is 110V & 240V switchable  
12V, 14V and 16V AGM IntelliCHARGER, Compatible 5A, 15A and 25A (25AMP Max Output), Three Charging Modes



**PSC IntelliSUPPLY** \*15A, 30A and 60A Models Available  
12V, 14V and 16V Compact High Frequency IntelliSUPPLY with AGM charge mode. 15A, 30A and 60A Models Available



**TB-604v2**  
600 Series Aluminum Terminal Blocks, 1/0, 4 Spots, M6/M8 Bolts. 2, 6, 8 Spot Designs In Copper And Aluminum Are Available.



**Fuse/Holder**  
ANL, 1/0 to 4AWG, Fuse Holder - Silver Finish and Clear Cover. 150A, 200A, 250A, 300A and 350A Fuses Available



**XS Flex / True AWG** 100% Pure Oxygen Free Tinned Copper

The **XS Flex** line of power cable is XS Power's flagship power cable. It is available in **Blue (XS FLEX0BL-50)**, **Clear (XS FLEX0CL-50)**, **Black (XS FLEX0BK-50)** and **Red (XS FLEX0RD-50)** in spools, 20ft, 5ft and 1ft increments. The **XS Flex** cable is 100% Pure Oxygen Free Tinned Copper Cable with a massive 4,704 strand count. Just like everything else XS Power does the **XS Flex** cable exceeds the industry CEA-2015 cabling standards and is True AWG cable. The high strand count and soft touch cable jacket allows the wire to be super flexible and easy to use in any installation. Both **XS Flex** cables are also available in a 1,862 strand count 4 AWG.

Distributed by:



XSPowerBATTERIES.COM • 888.4XSPower  
2847 John Deere Dr. #102 Knoxville, TN 37917

Please note that product specs are subject to change. For the most up-to-date information regarding any XS Power Batteries product, please refer to xspowerbatteries.com