

PRODUCT SPECSHEET

Product Name

VTOMAN Jump 1500X Power Station

Model Number

PB-22

UPC/Bar Code

782917487609



Product Features

- Powerful & compatible
- Expandable Capacity
- 12 ports, power whatever you like
- Enhanced Safety & Endurance
- 55,000 hours super-long performance
- Exclusive V-Beyond Technology
- 3 input Modes

DETAILED DESCRIPTION

- **Powerful & compatible:** Jump 1500X boasts 1500W super-strong output power and unique V-beyond Technology, compatible with appliances and devices like electronic stove, microwave oven, AC, and fridge. Total instant output adds up to 3000W.
- **Expandable Capacity:** Buffed by an 1548Wh extra battery, Jump 1500X is expandable to as large as 2376Wh in capacity.
- **12 ports, power whatever you like:** Jump 1500X features a pure sine wave inverter and multiple outlets, including: 3* AC outlet, 4*USB-A ports, 2*USB-C, 2* DC ports, and 1*car port to run low to high power appliances.
- **Enhanced Safety & Endurance:** VTOMAN LIFE BMS™ system guarantees enhanced battery performance and health.
- **55,000 hours super-long performance:** Powered by premium LFP battery, Jump 1500X offers over 3,000 battery charge circles which adds up to at least 55,000 hours of battery performance --- 6 Times better than the industry's average.
- **Exclusive V-Beyond Technology:** You can directly jump start your vehicles by connecting your car and the power station with a pair of jump start clamps* (sold separately).
- **3 input Modes:** 200W max solar panel input, 180W AC input and car input. Choose whichever way you like to fast and flexibly recharge your Jump 1500X.

PRODUCT SPECIFICATIONS

-BATTERY INFO

Capacity: 828Wh

Cell Chemistry: LiFePO4

Lifecycle: 3000+ cycles to 80%

Shelf-Life: 5 Years

Management System: LifeBMS, Over Voltage Protection, Temperature Protection, Over Charge Protection, Short Circuit Protection, Over-Current Protection, Over Discharge Protection etc.

DOD(Depth of discharge): 90%

-OUTPUT

AC Outlets x 3: continuous 1500W,Peak 3000W, 110V~60Hz, Pure Sine Wave

USB-A x 3: 5V 2.4A, 12W Max per port

USB-A x 1: 5V 3A, 9V 2A, 12V 1.5A, 18W Max

USB-C x 2: 5V 3A, 9V 3A, 12V 3A, 15V 3A, 20V 3A, 20V 5A 100W Max

DC5521 x 2: 12V 10A, total 120W for all DC ports

Car Charger x 1: 12V 10A, total 120W for all DC ports

12V Jump Starter x 1: Starting Current 500A; Peak Current 2000A

-INPUT

DC5521 x 1: DC12-30V (200W Max)

Car Cigarette Lighter Port x 1: 12/24V

Solar: 200W Max

-GENERAL INFORMATION

Net Weight: 36.2lbs (16.43kg)

Dimensions (LxWxD): 14.2×10.6×11.1 inches (360×270×280mm)

Simultaneous Recharge & Discharge: Yes

Operating Temperature: 14°F~113°F(-20°C~55°C)

Recharging Temperature: 32°F~113°F(0~55°C)

WHAT'S IN THE BOX

Jump 1500X Power Station X 1

Car Charger Cable X 1

AC Charger & Charging Cable X 1

USB-C to USB-C Cable X 1

USB-A to USB-C Cable X 1

User Manual X 1